













BT-Pusher BlueTooth Marketing Device Selection Guide

BT-Pusher BlueTooth Marketing Device Selection Guide										
Model Name	BT-Pusher STANDALONE	BT-Pusher PRO	BT-Pusher PRO with WiFi	BT-Pusher PRO with 3G	BT-Pusher PROE	BT-Pusher PROE with WiFi	BT-Pusher PROE with 3G	BT-Pusher PRO+	BT-Pusher PRO+ with WiFi	BT-Pusher PRO+ with 3G
Appearance										
Size	10*14*3cm	13*16*2.5cm			12*14*3cm			13*13*3cm		
Weight	300g	580g	600g	600g	500g	530g	530g	530g	550g	550g
Bluetooth Modules Type	Class I Module				Long Ranger Bluetooth Module with Amplifier			Long Range Bluetooth Module with Amplifier		
Range	100 Meter	100 Meter	100 Meter	100 Meter	200 Meter	200 Meter	200 Meter	300 Meter	300 Meter	300 Meter
Simultaneous connections	21	28 expanded to 42	28 expanded to 42	28 expanded to 42	28	28	28	28	28	28
Storage Size	128MB	128MB	128MB	128MB	128MB	128MB	128MB	128MB	128MB	128MB
Adjustable bluetooth Coverage Range by software settings(New Function)	√	√	√	√	√	√	√	√	√	√
USB Interface	√	√	√	√	√	√	√	√	√	√
LAN,WAN	X	√	√	√	√	√	√	√	√	√
WIFI	X	X	√	X	X	√	X	X	√	X
3G, GPRS	X	X	X	√	X	X	√	X	X	√
StandAlone Work Function	√	√	√	√	√	√	√	√	√	√
Abnormal automatic recovery function	√	√	√	√	√	√	√	√	√	√
Off-line USB Management	√	√	√	√	√	√	√	√	√	√
On-line Network Management	X	√	√	√	√	√	√	√	√	√
Antenna	Built-in Antenna				External Antenna (default :6db)			External Antenna (default :6db)		
Power supply	100V-240V Power Plug(Optional 4800mAh Lithium Battery PACK,or Car Power Interface)									
Operational Temperature	-10°C to +60°C									
Function	<ul style="list-style-type: none"> ● StandAlone Work Function ● Auto search for Bluetooth devices ● Support Adjustable bluetooth Coverage range by software settings ● Support world time(except BT-Pusher STANDALONE) ● Support for a variety of Bluetooth message transmission strategy ● It can be networked(seamless) and has a data-base which can be shared with other devices in a same network ● It can be monitored from remote distance over internet by wired(LAN,WAN) or wireless(3G,GPRS or WIFI) ● Blacklist function ● A variety of refuse retransmission mechanism ● Auto pair with bluetooth enabled devices(mainstream mobile models) ● Show the system working status using LED ● Delivery of a wide range of information type:txt,gif,jpg,mp3,mp4,3gp,java games and so on ● Support up to 56 Bluetooth devices at the same time to download ● Send bluetooth message at scheduled times ● File update at scheduled times ● The fastest download speeds of up to 150KByte/S , decided to Bluetooth version of mobile and receive environmental ● Transmission distance: up to 500 meters ● Support for different time periods to send different content ● The same user will get each message only ONCE ,no matter what version you're using ● System can automatically record connection and receive detailed information of all users for you to decision-makin ● Support Network Remote Management:LAN,WAN,WIFI,3G,GPRS and usb local management ● Support Abnormal automatic recovery function 									

[Http://www.BT-Pusher.com](http://www.BT-Pusher.com)



DeviceGate Technology Co.,Ltd
BT-Pusher is a Trade Mark of DeviceGate

Web: <http://www.BT-Pusher.com> <http://www.bt-pusher.com.cn>
 Add: Room 4032,HaoJing Building,NO.9 DaGangGongYe Road, TianHe , GuangZhou, GuangDong, China
 Mail: Sales@BT-Pusher.com
 Tel: 0086-20-82317785, 0086-20-82317786
 Fax: 0086-20-62201638